


- | | |
|--------------------|---------------------|
| 10.000 – CR 4 M5 | 10.007 – CR 10 1/4" |
| 10.001 – CR 4 1/8" | 10.008 – CR 10 3/8" |
| 10.002 – CR 6 1/8" | 10.009 – CR 10 1/2" |
| 10.003 – CR 6 1/4" | 10.010 – CR 12 1/4" |
| 10.004 – CR 8 1/8" | 10.011 – CR 12 3/8" |
| 10.005 – CR 8 1/4" | 10.012 – CR 12 1/2" |
| 10.006 – CR 8 3/8" | |



Conector recto

Modelo	10.000 al 10.012 - CR...-...
Fluido	Aire, Vacio y Liquidos
Rango de Presión	- 0,75 a 10,2 bar
Vacio	- 0,750 mm Hg (10 Torr)
Presión Máxima	15,3 bar
Conexión	Rosca de M5 a 1/2"
Diametro de Manguera	de 4 mm a 12 mm
Temperatura	0 a 60 °C



CODIGO	MODELO	D1	D2	L1	L2	LLAVE	ALLEN
10.000	CR 4 M5	4	M5	21,5	2,6	10	
10.001	CR 4 1/8"	4	1/8"	22	4,2	10	3
10.002	CR 6 1/8"	6	1/8"	26,1	5,2	12	4
10.003	CR 6 1/4"	6	1/4"	22,5	5,6	12	5
10.004	CR 8 1/8"	8	1/8"	22,8	6,4	14	5
10.005	CR 8 1/4"	8	1/4"	26,1	6,1	14	6
10.006	CR 8 3/8"	8	3/8"	24,4	8,1	14	6
10.007	CR 10 1/4"	10	1/4"	30,6	5,6	17	6
10.008	CR 10 3/8"	10	3/8"	29,8	9,7	17	8
10.009	CR 10 1/2"	10	1/2"	31,2	8,9	17	8
10.010	CR 12 1/4"	12	1/4"	31	6,8	21	6
10.011	CR 12 3/8"	12	3/8"	28	7,4	21	10
10.012	CR 12 1/2"	12	1/2"	32,4	10,2	21	8

Dineu S.A.

9 de Julio 1572 Ciudadela, Buenos Aires, Argentina

CP: 1702

Tel/Fax: (011) 5648-7272

Tel: (011) 5648-7373

ventas@dineu.com.ar

www.dineu.com.ar

DiNeu